

The VB series is made up of vertical vibrators which feature a double conical flange. These vibrators are typically used in circular screens and in medium-size and large sieves.

They are supplied without eccentric weights, which must be realised and mounted by the manufacturer of the vibrating machine.

The VB series complies with the most recent IEC and EN international standards for use in atmospheres with potentially explosive dust particles. In particular, the VB series can be used in areas 21 and 22.

### Technical features

**Power supply**

Three-phase voltage from 220V to 690V, 50Hz or 60Hz; suitable for use with an inverter from 20Hz to the base frequency with constant torque load profile

**Polarity**

4 and 6 poles.

**Conformity with Standards and Regulations**

Low Voltage Directive 2006/95/EC; ATEX Directive 2014/34/UE; EN/IEC 60034-1, EN/IEC 60079-0, EN/IEC 60079-31, UL 1004-1, CSA C22.2 No.100, NEMA MG-1.

**Functioning**

Continual service (S1) at maximum declared centrifugal force and electric power. Intermittent services are also possible depending on the type of vibrator and the operating conditions. For detailed information, contact our technical assistance office.

**Centrifugal force**

Proportioned for a centrifugal force equal to 5000 kgf. (49 kN), with eccentric weights not included, to be made by the user.

**Mechanical protection**

IP 66 according to IEC/EN 60529.

**Protection against mechanical impacts**

IK 08 according to IEC/EN 62262.

**Insulation class**

Class F (155°C), class H (180°C) on request.

**Tropicalization**

Standard on all vibrators with "drop by drop" trickle system.

**Ambient temperature**

From -20°C to +40°C. Versions for higher or lower temperatures are available on request.

**Vibrator thermal protection**

Standard PTC rated thermistor heat detectors 130°C for VB 15/5000-LM, on request for smaller sizes. Also on request thermistors with different temperatures, bimetallic thermal protections and anti-condensation heaters.

**Fixing of the vibrator**

Typical vertical assembly with double tapered flange.

**Lubrication**



All vibrators are lubricated in the factory and do not require further lubrication at start-up.

**Terminal box**

The size guarantees passage of tools used for fixing the vibrator to the vibrating machine. The electrical connection must be carried out using the relative connectors inserted inside the connection box. Special shaped terminals allow to fix the power supply cable, protecting it from loosening.

## 6 poles - 1.000/1.200 rpm

### Three-phase

DESCRIPTION		MECHANICAL SPECIFICATIONS								ELECTRICAL SPECIFICATIONS					
Code	Type	  II2D Temp. class	rpm		Centrifugal force				Weight kg	Max input power		Max current		Ia/In	
			50Hz	60Hz	50Hz	60Hz	50Hz	60Hz		W	400V 50Hz	460V 60Hz	50Hz	60Hz	
602171	VB 10/2510-D	• 150°C	-	1200	-	2500	-	24,5	68,0	-	2100	-	3,22	-	3,27
602056	VB 10/5500-D	-	-	1200	-	5500	-	54,0	110	-	4600	-	7,70	-	5,00

## Certifications

**Category:** II 2 D

**Level of protection:**

Ex tD A21 T...°C IP66 (Ex tb IIIC T...°C Db)

**Temperature class:**

see tables

**Zones of use:**

21, 22



Compliance with the applicable European Union directives.



Standard CAN/CSA – C22.2, N°.100-95, Certificate n° LR 100948  
Class 4211 01 - Motors and generators  
UL 1004-1 – Rotating Electrical Machines – General Requirements



II2D (2014/34/UE)  
Ex tD A21 T...°C IP66 (Ex tb IIIC T...°C Db)  
EN 60079-0  
EN 60079-31



Ex tD A21 T...°C IP66 (Ex tb IIIC T...°C Db)  
IEC 60079-0  
IEC 60079-31



Version VB-C available on request  
Class I Div.2, Groups ABCD  
Standard CAN/CSA – C22.2



Certification for Eurasian Customs Union  
N° TC N RU Д-IT.АЛ33.В.02527  
N° TC RU C-IT.ГБ08.В.02190



KOSHA Korea  
Certificate n° 11-AVG BO-0359  
Ex td A21 IP66

### Electric motor

Three-phase asynchronous type. Designed for maximum starting torques and torque curves specific to requirements of vibrating machines. Insulated windings using “drop by drop” trickle system with class H resin. The rotor is die cast aluminium.

### Casing

In spheroidal cast iron to have high strength and optimal elasticity.

### Bearing flange

The two flanges, made in spheroidal cast iron, are characterized by external tapered diameter for fixing in the vibrating machine.

### Bearings

Custom made with particular geometry, especially designed for Italvibras, suitable to support both high radial and axial loads.

### Motor shaft

In treated steel alloy (Isothermic hardening) resistant to stress. On request both shaft ends may be modified to be adapted to the user weights.

### Eccentric weights

Not envisioned, to be made and mounted by the user.

### Weight covers

Not envisioned.

### Painting

Electrostatic surface treatment based on polymerised epoxy polyester powder in oven at 200°C. Tested in salt spray for 500 hours.

### For further details please contact sales

offices at Italvibras.

**The technical data and models listed in this catalogue are not binding. Italvibras reserves the right to modify them without prior notice.**




Fig. H

### DIMENSIONAL SPECIFICATIONS (mm)

VB 10/2510-D	H	517,5	281	158,5	27	23	14	82,5	127	41,5	108	M32x1,5
VB 10/5500-D	H	607	282,5	216	25	25	14	119	143,5	38,0	90,5	M32x1,5

la/In = ratio between start-up current and maximum current.