



INTERNAL CONCRETE VIBRATORS

HX, AW, AX

- Highly portable hand held vibrator
- Four stroke Honda GX35 engine, Lower emissions than two stroke equivalent
- Lower emissions than two stroke equivalent
- Electric Unit also available
- Ideal for working in areas of limited access
- Backpack with zipped toolholder
- Throttle control on backpack
- Centrifugal Clutch



BX Backpack	
Model	BX-GX35
Type	Backpack
Engine	Honda GX35 4 stroke
Motor Speed	7000-9000 rpm
Unit weight	

AX Poker / AXD Drives / Couplings Type D

Model	AD45/2	AD45/3
Head diameter/mm	45mm	45mm
Head length/mm	325	325
Head weight/kg	3.0 kg	3.0 kg
Drive length	3 mtr	3 mtr
Drive Speed /rpm	9000	9000
Shaft x cover/mm	8 x 28	8 x 28
Drive weight /kg	4.0kg	5.0kg
Poker & Drive Weight	6.6 kg	7.6 kg
Frequency /rpm	9000	9000
Amplitude	2.0	2.0
Centrifugal Force Newtons	4190	4190
Centrifugal Force /Kg	420	420
Weighted vibration m/s ²	1.45	1.45
Output maximum m ³ /h	28	28
Radius of effectiveness cm	43	43
S P Level dB(A)	95dB(A)	95dB(A)



Performance figures are all theoretical based on a new machine, but may vary due to different types of concrete and should only be used as a guide

VIBRATECHNIQUES LTD

20 Cecil Pashley Way, Shoreham Airport, Shoreham by Sea, West Sussex, BN43 5FF
Tel: +44 (0)1273 430977 Fax: +44 (0)1273 430978 Email: sales@vibtec.com Web: www.vibtec.com