



**INTERNAL CONCRETE VIBRATORS**

**M4P, VPI, VPK**



High Frequency Immersion Vibrator

Heavy Duty Construction,

Oil Cooled and Lubricated

Full motor protection with Thermo Control

Electric motor close coupled to an eccentric mass

42 volts 3 phase 200 Hz

Supplied with 5m of handling hose

Aluminium Switch box

10m of heavy duty flexible cable and 32 / 63 amp plug

VPI65H Special High Performance with Low amperage

Frequency Convertors and Generators available

### VPI HIGH FREQUENCY ELECTRIC IMMERSION VIBRATORS

Model	VPI31	VPI39	VPI51	VPI59	VPI65H	VPI66	VPI81
Input Voltage	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200
Current (Start up +15%)Amps	8.0	10.0	18.00	25.0	28.0	30.0	55.0
Head Diameter mm	31	38.5	51	59	65	66	81
Head Length mm	320	370	390	360	340	510	445
Hose size mm x mm	18 x 29	20 x 33	25 x 40	25 x 40	25 x 40	25 x 40	32 x 49
Hose length	5	5	5	5	5	5	5
Cable Length	10	10	10	10	10	10	10
Total Weight kgs	8.1	9.8	14.6	15.4	16.8	18.7	29.0
Frequency vpm	12000	12000	12000	12000	12000	12000	12000
Centrifugal Force Newtons	1400	1600	3600	5400	7200	7200	15200
Centrifugal Force Kg	142	163	367	550	734	734	1549
Weighted Vibration m/s <sup>2</sup>	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5
Output Maximum m <sup>3</sup> /hr	12	15	21	36	38	38	60
Radius of Effectiveness cm	37.2	46.8	67.2	70.8	78.0	78.0	97.2
S P Level d(b)A	<72	<72	<72	<72	<72	<72	<72
CEE Plug	32	32	32	32	32	32	63

## VIBRATECHNIQUES LTD

20 Cecil Pashley Way, Shoreham Airport, Shoreham by Sea, West Sussex, BN43 5FF  
Tel: +44 (0)1273 430977 Fax: +44 (0)1273 430978 Email: sales@vibtec.com Web: www.vibtec.com



High Frequency Immersion Vibrator  
Heavy Duty Construction, Oil Cooled  
Full motor protection with Thermo Control  
Electric motor close coupled to an eccentric mass  
42 volts 3 phase 200 Hz  
Supplied with 5m of handling hose  
Aluminium Switch box  
10m of heavy duty flexible cable and 32 / 63 amp plug  
VPI65H Special High Performance with Low amperage  
Frequency Convertors and Generators available

**VPI-H HIGH FREQUENCY ELECTRIC IMMERSION VIBRATORS**

Model	VPI-H 31	VPI-H39	VPI-H51	VPI-H59	VPI-H65H	VPI-H66	VPI-81
Input Voltage	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200	42/3/200
Current (Start up +15%)Amps	8.0	10.0	18.00	25.0	28.0	30.0	55.0
Head Diameter mm	31	38.5	51	59	65	66	81
Head Length mm	320	370	390	360	340	510	445
Hose size mm x mm	18 x 29	20 x 33	25 x 40	25 x 40	25 x 40	25 x 40	32 x 49
Hose length	0.8	0.8	0.8	0.8	0.8	0.8	0.8
Cable Length	15	15	15	15	15	15	15
Total Weight kgs	8.1	9.8	14.6	15.4	16.8	18.7	29.0
Frequency vpm	12000	12000	12000	12000	12000	12000	12000
Centrifugal Force Newtons	1400	1600	3600	5400	7200	7200	15200
Centrifugal Force Kg	142	163	367	550	734	734	1549
Weighted Vibration m/s <sup>2</sup>	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5	<2.5
Output Maximum m <sup>3</sup> /hr	12	15	21	36	38	38	60
Radius of Effectiveness cm	37.2	46.8	67.2	70.8	78.0	78.0	97.2
S P Level d(b)A	<72	<72	<72	<72	<72	<72	<72
CEE Plug	32	32	32	32	32	32	63

**VIBRATECHNIQUES LTD**

20 Cecil Pashley Way, Shoreham Airport, Shoreham by Sea, West Sussex, BN43 5FF  
Tel: +44 (0)1273 430977 Fax: +44 (0)1273 430978 Email: sales@vibtec.com Web: www.vibtec.com