



SURFACE FINISHING

STANDARD SCALING HAMMER TWO PIECE PISTON

Standard Two piece scaling Head Hammers



SF1 was formerly designated as SS1, and SF3 was formerly designated as TS3.

Low Vibration

SF1 is available with low vibration handle



T. C.T Cruciform Head

Detachable taper fit head.

Used on steel surfaces for removal of thick coatings, heavy rust and scale.

Most commonly used head.



T.C.T Bush Hammer Head

Detachable taper fit head

Used for laitance removal and exposing the aggregate in concrete. Leaves a profile when used for scabbling



Beryllium Copper Head

Detachable taper fit head

Used on steel surfaces for removal of thick coatings, heavy rust and scale. Can be used safely in combustible areas

Type	SF1 Standard Single Headed Scabbler	SF2 Standard Triple Headed Scabbler
Part Number	Formerly SS1	Formerly TS3
TCT Bush Hammer Piston	070312	070316
TCT Cruciform Head	070311	070313
Piston Diameter / Stroke	27mm / 22.5 mm	27mm / 22.5mm
Piston Type as Standard	TCT Cruciform	TCT Cruciform
Blows per Minute	3000	3 x 3000
Air Consumption (at 6.3 bar / 90 p.s.i)	2.4 litres / Second 5 cubic feet/minute	5.2 litres / Second 11 cubic feet/minute
Length	460 mm	472 mm
Weight	2.4kg	3.5kg
Noise Level	92 dB(A)	92 dB(A)
Vibration Level	6.8 m/s ²	13.4 m/s ²

Features

- Cruciform, Tungsten carbide tipped heads
- Self closing lever throttles.
- Quick release throttle lock 3/8 inch N.P.T air inlet

Applications

- Removal of rust, coatings, scale from steel structures and surfaces.
- Cleaning of cast iron, steel pipe and bell joints of gas lines maintained by utilities and gas companies
- Removal of stubborn coatings and mastic residue from floor.

VIBRATECHNIQUES LTD

20 Cecil Pashley Way, Shoreham Airport, Shoreham by Sea, West Sussex, BN43 5FF

Tel: +44 (0)1273 430977 Fax: +44 (0)1273 430978 Email: sales@vibtec.com Web: www.vibtec.com