



SURFACE FINISHING

Long reach SC1M Scabblers and Compactors supplied with Scabbling Heads and Tamper Feet to suit most applications. They are a powerful tool for deep concrete dressing and for filler tamping.

Features:

Angled Air Inlet:




- For operator safety
- Situated below the throttle for better maneuverability

Selection of Heads available



Part Number	150.5013	150.0000	150.0000
Head	5 Point	9 Point	Cruciform
Blows per Minute	3400		
Air Consumption (at 6.3 bar / 90 p.s.i)	11.6 litres / Second 25 cubic feet/minute		
Handle Type	Straight		
Length	1346 mm		
Weight	13.5kg		
Air Inlet	1/2" BSP		

SCABBLING HEADS 2 1/4" 57mm

5 Point TCT	9 Point TCT	Cruciform
		
Best suited to concrete reduction and for laitance removal, these may reduce the likelihood of damage to the aggregate ensuring that a stronger bond is created with the next fill or finish layer.	Best suited to concrete reduction and for laitance removal, these may reduce the likelihood of damage to the aggregate ensuring that a stronger bond is created with the next fill or finish layer. Higher production rate than five point.	Reduction of Concrete or where a smoother finish is required, these will reduce the aggregate as well as the concrete surface leaving a relatively flat surface, these are also suitable for the removal of epoxy coatings.

COMPACTION FEET

127 mm	100 x 100 mm	127 x 157 mm	100 x 200 mm
			
General Compaction Work	Standard Foot for all tamping jobs	Tamping Close to Walls and street fittings	Narrow Trench Work carried out by Cable Companies

VIBRATECHNIQUES LTD

20 Cecil Pashley Way, Shoreham Airport, Shoreham by Sea, West Sussex, BN43 5FF

Tel: +44 (0)1273 430977 Fax: +44 (0)1273 430978 Email: sales@vibtec.com Web: www.vibtec.com